

0 601 19C 600 – GSB 21-2 RE


Material number	0 601 19C 600
EAN	3165140519533
Baretool number	3601A9C600
Auxiliary handle 2 605 025 193	✓
Carrying case 2 605 438 524	✓
Depth stop 210 mm 1 613 001 010	✓
Keyed chuck 13 mm 2 608 571 068	✓
Voltage, electrical	230 V



Technical data

Technical Data

Rated power input	1100 W
No-load speed	0 - 900 / 3000 rpm
Power output	630 W
Weight	2,9 kg
Rated speed	0 - 580 / 1900 rpm
Torque (soft screwdriving applications)	40,0 / 14,5 Nm
Rated torque	9,6 / 3,2 Nm
Drill spindle connecting thread	1/2" – 20 UNF
Chuck capacity, min./max.	1,5 - 13 mm
Impact rate at no-load speed	0 - 15300 / 51000 bpm
Max. torque	40,0 / 14,5 Nm



Drilling range

Drilling diameter in concrete	22 / 13 mm
Drilling diameter in wood	40 / 25 mm
Drilling diameter in steel	16 / 8 mm
Drilling diameter in masonry	24 / 16 mm

Sales information

Key Message

- The most powerful tool in its class – for the toughest applications

User benefits

- Bosch high-performance motor (1100 W) with high torque for the most heavy-duty applications with large diameters (drilling, working with core cutters and holesaws), screwdriving and stirring
- Sturdy metal gear housing for a long lifetime
- Antirotation mechanical overload clutch for a high level of work safety, even in the toughest applications

Other features

- Single-sleeve keyless chuck with Auto-Lock for quick bit changes with only one hand
- New safety handle with innovative fixing and softgrip for a secure hold on the machine
- Speed preselection with setting wheel for precise working
- Rotating brush plate for equal power in reverse and forward rotation
- Ball grommet for high movement radius and for preventing cable breaks
- Spindle collar diameter of 43 mm (European standard) – can be used in drill stands

