

# 0 601 217 1F3 – GSB 13 RE

Material number	0 601 217 1F3	0 601 217 1F6	0 601 217 1F8
EAN	3165140548106	3165140568593	3165140596138
100 pcs accessory set		✓	
Auxiliary handle 1 602 025 024	✓	✓	
Depth stop 210 mm 1 613 001 010	✓	✓	
Keyed chuck 13 mm 2 608 571 079	✓	✓	
Tool box 2 609 160 136			✓
Baretool number			3601B171F4



## Technical data

### Technical Data

Rated power input	600 W
No-load speed	0 - 2800 rpm
Power output	301 W
Weight	1,7 kg
Torque (soft screwdriving applications)	10,8 Nm
Rated torque	1,8 Nm
Drill spindle connecting thread	1/2"-20 UNF
Chuck capacity, min./max.	1,5 - 13 mm
Length	266,0 mm
Height	180,0 mm
Impact rate at no-load speed	0 - 44800 bpm



### Drilling range

Drilling diameter in concrete	13 mm
Drilling diameter in wood	25 mm
Drilling diameter in steel	10 mm
Drilling diameter in masonry	15 mm

## Sales information

### Key Message

- Compact power – The most compact and powerful impact drill in its class

### User benefits

- Robust and powerful 600 W motor
- Extremely handy: no bigger than a glove and 1.7 kg light
- Soft in line grip for a secure hold

### Other features

- Speed trigger with electronic control for exact pilot drilling
- Rotating brush plate for constant power in reverse and forward rotation
- Higher dynamic load rated ball bearing for long life
- Auxiliary handle with depth stop for better control