

| | | |
|--------------------------------------|---------------|---------------|
| Material number | 0 601 27A 3F0 | 0 601 27A 300 |
| EAN | 3165140893398 | 3165140893350 |
| Baretool number | 3601B7A3F0 | 3601B7A300 |
| Grinding wheel, normal grit, grit 24 | ✓ | ✓ |
| Grinding wheel, normal grit, grit 60 | ✓ | ✓ |

Technical data

Technical Data

| | |
|-------------------------|----------|
| Grinding wheel diameter | 150 mm |
| No-load speed | 3000 rpm |
| Grinding wheel widths | 20 mm |
| Grinding wheel bore | 20 mm |
| Grit | 24 60 |
| Rated power input | 350 W |
| Rated speed | 3000 rpm |
| Weight | 10,0 kg |
| Length | 325 mm |
| Width | 175 mm |
| Height | 200 mm |



Sales information

Key Message

- The powerful and sturdy tool for toughest applications

User benefits

- Powerful induction motor for various working conditions and usages
- Compact die-cast housing with encapsulated ball bearings to keep the motor free of dust
- Robust and solid base for longevity and stable working conditions

Other features

- Large and easily-adjustable spark protection glasses for safe and precise work
- Sturdy adjustable workpiece supports for precise jobs
- Rubber feet securing a low-vibration standing
- Dust-protected on/off switch to prevent dust coming into switch to ensure a long lifetime
- Easy wheel change for efficient and easy work