

# 0 601 9B9 1F0 – GDX 18 V-EC

|   |               |               |
|---|---------------|---------------|
| Material number   | 0 601 9B9 1F0 | 0 601 9B9 100 |
| EAN   | 3165140765015 | 3165140661928 |
| Solo-Version  | 0.0           | 0.0           |
| Works with battery capacity                               | 4,0 Ah        | 4,0 Ah        |
| Battery voltage   | 18.0 V        | 18.0 V        |
| Weight incl. battery                                      | 1,7 kg        | 1,7 kg        |
| Baretool number   |               | 3601JB9100    |
| 1/2 L-BOXX inlay for accessories<br>1 600 A00 2WC         |               | ✓             |
| 1/2 L-BOXX inlay for tool and<br>charger<br>1 600 A00 2WB |               | ✓             |
| 2 x 4.0 Ah Li-Ion battery<br>1 600 Z00 038                |               | ✓             |
| L-BOXX 136<br>1 600 A00 1RR                               |               | ✓             |
| Quick charger AL 1860 CV<br>2 607 225 322                 |               | ✓             |



## Technical data

### Technical Data

|                                       |  |
|---------------------------------------|--|
| Works with battery capacity           | 4,0 Ah   |
| No-load speed                         | 0 - 2.800 rpm                                  |
| No-load speed (1st level / 2nd level) | 1100 – 2600 / 3200 rpm                         |
| Torque, max.                          | 185 Nm   |
| Rated impact rate                     | 0 - 3200 bpm                                   |
| Length                                | 158,0 mm                                       |
| Height                                | 240,0 mm                                       |
| Battery voltage                       | 18 V   |
| Bit holder                            | 1/4" internal hexagon and 1/2" external square |

### Screw diameter

|                |            |
|----------------|------------|
| Screw diameter | M 6 – M 16 |
|----------------|------------|



## Sales information

### Key Message

- The most universal impact driver in its class – with even longer lifetime

### User benefits

- Special bit holder combines 1/2" square and 1/4" hexagon – for even more applications
- Brushless EC motor technology from Bosch – for up to 100% longer lifetime
- Very compact design for perfect handling, even in the tightest spaces and overhead

### Other features

- 3-stage PowerControl – for different torques in a wide variety of applications
- Speed can be set to 0 – 1300/2000/2800 rpm
- Impact rate can be set to 0 – 1100/2600/3200 bpm