

## TIG Torches - Air / Water Cooled

**TXH 150/200 4/8m Air Cooled**

**TXH 250w/400w/400w HD 4/8m Water Cooled**

**TXH 150r/200r 4/8m Air Cooled with Remote Functions**

**TXH 250w/400w/400w HD 4/8m Water Cooled with Remote Functions**

**TXH 150V/200V 4/8m Air Cooled for Scratch TIG**

- Rugged construction - trouble free operation with minimum maintenance.
- Ergonomically designed handle.
- Effective cooling system.
- All torches come with OKC connection as standard.
- TXH 150r/200r/250wr/400wr/400wr HD TIG torches available with remote control for CAN-bus based TIG machines i.e. for Caddy Tig 2200i AC/DC, Origo Tig 3000i, Origo Tig 3000i AC/DC, Aristo Tig 4000i and Origo Tig 4300iw AC/DC.
- Gas valve mounted TIG torches TXH 150V/200V for scratch TIG using rectifiers.
- Wide range of wear parts e.g. collet, collet body, nozzle, and gas lens available for welding in all positions.
- All the TIG torches conform to international standard IEC/EN 60974-7.



Technical Data	TXH 150 / TXH 150r / TXH 150V	TXH 200 / TXH 200r / TXH 200V
Type of cooling	Air / Gas	Air / Gas
Connection	OKC 25 / 50	OKC 50
Size of TIG rod, mm	1.0 - 3.2	1.0 - 4.0
Rating, A@% duty cycle	150 @ 35%	200 @ 35%
Length, m	4 / 8	4 / 8

Technical Data	TXH 250w / TXH 250wr	TXH 400wr TXH 400w /	TXH 400w HD /
Type of cooling	Water	Water	Water
Connection	OKC 50	OKC 50	OKC 50
Size of TIG rod, mm	1.0 - 3.2	1.0 - 4.8	1.0 - 4.8
Rating, A@% duty cycle	250 @ 60%	400 @ 35%	430 @ 35%
Length, m	4 / 8	4 / 8	4 / 8