



Constructed from heavy gauge steel for heavy-duty use with a large diameter saddle for a secure hold under the jacking point. Extra long handle for easy access under bigger vehicles which also tilts and locks in three positions with a built-in handle mounted safety release to prevent accidental lowering of the load. A foot pedal pump and fine adjustment are fitted on the handle for optimum vehicle height. Automatic safety overload protection and rear toe plate for easy positioning.



Model Number	Max Load (kg/Tonne)	Min Height (mm)	Max Height (mm)	Saddle Ø (mm)	Handle Pieces (mm)	Handle Length (mm)	Chassis Length (mm)	Chassis Width (mm)	Chassis Height (mm)	Net Weight (kg)
T556	5,000/5	150	560	130	1	1,200	1,420	370	200	95.0
T1056	10,000/10	160	560	150	1	1,200	1,555	490	255	145.0

1 tonne (metric ton or t) = 1000kg.

1 ton (imperial ton) = 2240lbs (1016kg).

2 - 3 Days
Carriage at Cost

Model Number	Capacity	Order Code	List Price/1	Offer Price/1
T556	5 Tonne	-6380K	£640.89	£397.35
T1056	10 Tonne	-6420K	£971.20	£602.14

Spares		Order Code	Offer Price/1
Description	Order Code	KEN-567	
Handle Assembly to suit T556 & T1056	-7800K		£59.54

500kg Engine Support Beam

For supporting and accurately positioning engines during maintenance operations and as an aid for the removal of gearboxes and transmissions. 500kg (½ tonne) capacity. Adjustable width to bridge various engine compartments. Fitted with soft rubber feet to protect the bodywork. Supplied with a 92cm long chain. Supporting legs can be tilted.

Type	Capacity	Weight each	Order Code	List Price/1	Offer Price/1
Engine Support	500kg		-8100K	£119.95	£74.37

Group 582

1800mm

875mm

2 - 3 Days
Carriage at Extra Cost

Telescopic Transmission Jack

Ideal for car and light commercial transmission removal and installation. Fully adjustable universal rotary saddle with adjustable corner brackets and safety chains. Foot operated pump and release valve leaves both hands free to manoeuvre transmission. Wide base with four 3" dia. swivel-type ball bearing castors providing stability and easy manoeuvring. Two-stage flash chromed rams inhibit rust from entering the hydraulic system. Lifts from 875 to 1800mm.

Contents	TTJ500
Capacity	½ Tonne
Ram Extensions	2
Minimum Saddle Height	875mm
Maximum Saddle Height	1800mm
Saddle Size	680 x 810mm
Chain Length	95mm
Saddle Tilt Forward	24"
Saddle Tilt Back	19"
Saddle Tilt Side	±20"
Saddle Return Weight	15.8kg (35lbs)
Base	695 x 805mm
Weight	68.5kg

Model Number	Order Code	List Price/1	Offer Price/1
TTJ500	-7160K	£622.25	£385.80

Description	Order Code	Offer Price/1
Seal Repair Kit	-8210K	£72.62

HAND TOOLS