OBE 100mm **Angle Grinder**

Adjustable safety guard, safety lever throttle. Supplied with auxiliary side handle, flanges and spanners, lightweight and compact. 100 x 3 x 16mm cut-off disc.

Air inlet thread: 1/4" NPT. Spindle thread: 3/8" - 24. Minimum air hose size: 10mm (3/8"). Air pressure: 6.3bar (90psi). Air consumption: 6cfm* (216ltr/min). Motor power: 0.7hp.



115mm Angle Grinder

Suitable for grinding, cutting-off and sanding. Safety lever throttle. Supplied with auxiliary side handle, flanges and spanners. 115 x 3 x 22mm cut off disc.

Air inlet thread: 1/4" NPT. Spindle thread: M10 x 1.5mm. **Minimum air hose size:** 10mm (3/8"). **Air pressure:** 6.3bar (90psi). Air consumption: 6cfm* (216ltr/min).

Motor power: 0.7hp. Sound pressure level: 89dBA. Sound power level: 96dBA. Vibration level: 4.0m/s². Overall length: 240mm. *Based on a

Free Speed Weight Order Code List Offer each KBE-270 Price/1 Price/1 (rpm) 11.000 1.80kg -2060Q £208.06£145.64

Operator

Friendly

Composite

180mm Heavy Duty Angle Grinder

GA1807L

115 mm

Supplied with front exhaust, safety lever throttle, auxiliary side handle and adjustable safety guard. For grinding only.

Air inlet thread: 1/4" NPT. Spindle thread: 5/8" UNC. Minimum air hose size (ID): 10mm.

Air pressure: 90psi. Air consumption: 6½cfm* Sound pressure level: 103dBA. Sound power level: 109dBA.



Vibration level: 2.6m/s². Overall length: 340mm. *Based on a

15 second

Operato

Friendly

125

100

180

cycle per minute average use. Offer List

Free Speed Weight Order Code (rpm) each KBE-270 Price/1 Price/1 7.000 3.50kg -2070R £338.87£237.21

50mm Mini **Angle Grinder**

Free Speed Weight Order Code

each

FAG050M

TOOLS

POWER

Oğ

(rpm)

11.000

For metal dressing, rust removal, weld preparation and automotive bodywork fabrication in hard to reach areas. Speed regulator. Safety release throttle. Heavy duty disc guard. Side exhaust. Ball bearing construction. Supplied with: 2x A60 (KEN230-0040K), 1x A80 (KEN230-0050K) and 1x A120 (KEN230-0060K) 50mm grinding discs.

List KBE-270 Price/1 Price/1

1.80kg -2050P £174.07£121.85

Offer



		The second second		manaic on p
Free Speed (rpm)	Weight each	Order Code KBE-270	List Price/1	Offer Price/1
20,000	530g	-2090K	£102.95	£72.07

76mm Reversible Cut-off Tool **FCT076**

15 second cycle

per minute

average use.

For cutting auto panels, light sheet metal, fibreglass, nuts and bolts. Powerful 0.5HP motor. Speed regulator. Safety release throttle. Rear exhaust. Rotating air inlet. Reverse feature. Ball bearing construction.



103dBA. Vibration level: 0.5m/s². Overall length: 185mm.

per minute average use. Offer List Price/1

*Based on a 15 second cycle

Free Speed Weight Order Code KBE-270 Price/1 (rpm) 18,000 950g -1200K £90.16 £63.11

115 & 125mm Angle Grinder

Suitable for metal dressing, rust removal, weld preparation and automotive bodywork fabrication. and automotive bodywork fabrication. Rubber-cushioned side handle provides grip and operator comfort.

Free speed: 10,000rpm (governed). Air inlet thread: 1/4" NPT. Spindle thread: M14 x 2.0mm. Minimum air hose size: 10mm (3/8").



cycle per minute average u				rage use.			
Model	Disc	Free Speed				Offer	
Number	Size	(rpm)	each	KBE-270	Price/1	Price/1	
FGA120g	115mm (4½")	10,000	1.95kg	-1960K	£217.33	£152.13	
FGA130g	125mm (5")	10 000	1 96kg	-1980K	£218 36	£152 85	

Chicago Heavy Duty Pneumatic Angle Grinders

Aluminium alloy housing, spiral bevel gearing, removable dead handle. Supplied with auxiliary side handle, lightweight and compact.

Motor power: 0.6hp. Air inlet: 1/4" NPT. Minimum air hose size: 10mm (3/8"). Air pressure: 90psi. Air consumption: 6cfm. Spindle thread: 3/8" - 24 (CP854), 10mm x 1.5P (CP854E).

Overall length: 229mm.



Model Number	Size	Free Speed (rpm)			List Price/1	Offer Price/1
CP854	4" (100mm)	12,000	1.7kg	-8045V	£339.05	£237.34
CP854E	5" (125mm)	12,000	1.7kg	-8045N	£339.05	£237.34